

Abstract Data Types

Abstract Data Types

- Typical operations on data
 - Add data to a data collection
 - Remove data from a data collection
 - Ask questions about the data in a data collection
 - Data abstraction
 - Asks you to think *what* you can do to a collection of data independently of *how* you do it
 - Allows you to develop each data structure in relative isolation from the rest of the solution
 - A natural extension of procedural abstraction
-

Abstract Data Types

- Abstract data type (ADT)
 - An ADT is composed of
 - A collection of data
 - A set of operations on that data
 - Specifications of an ADT indicate
 - What the ADT operations do, not how to implement them
 - Implementation of an ADT
 - Includes choosing a particular data structure
 - A data structure is a construct that can be defined in a programming language to store a collection of data
-

Abstract Data Types-Walls




Figure 4-1

Isolated tasks: the implementation of task *T* does not affect task *Q*

Abstract Data Types

- The isolation of modules is not total
 - Methods' specifications, or contracts, govern how they interact with each other




Figure 4-2

A slit in the wall

Specifying ADTs



Figure 4-5

list A grocery

- In a list
 - Except for the first and last items, each item has
 - A unique predecessor
 - A unique successor
 - Head or front
 - Does not have a predecessor
 - Tail or end
 - Does not have a successor

The ADT List

- ADT List operations
 - Create an empty list
 - `aList.createList();`
 - Determine whether a list is empty
 - `aList.isEmpty();`
 - Determine the number of items in a list
 - `aList.size();`
 - Add an item at a given position in the list
 - `aList.add(index, item);`
 - Remove the item at a given position in the list
 - `aList.remove(index);`
 - Remove all the items from the list
 - `aList.removeAll();`
 - Retrieve (get) the item at a given position in the list
 - `aList.get(index);`
 - Items are referenced by their position within the list
-

Pseudocode for the ADT List Operations

```
+createList()  
// Creates an empty list.  
  
+isEmpty():boolean {query}  
// Determines whether a list is empty.  
  
+size():integer {query}  
// Returns the number of items that are in a list.  
  
+add(in index:integer, in item:ListItemType)  
// Inserts item at position index of a list, if  
// 1 <= index <= size()+1.  
// If index <= size(), items are renumbered as  
// follows: The item at index becomes the item at  
// index+1, the item at index+1 becomes the  
// item at index+2, and so on.  
// Throws an exception when index is out of range or if  
// the item cannot be placed on the list (list full).  
  
+remove(in index:integer)  
// Removes the item at position index of a list, if  
// 1 <= index <= size(). If index < size(), items are  
// renumbered as follows: The item at index+1 becomes  
// the item at index, the item at index+2 becomes the  
// item at index+1, and so on.  
// Throws an exception when index is out of range or if  
// the list is empty.  
  
+removeAll()  
// Removes all the items in the list.  
  
+get(index):ListItemType {query}  
// Returns the item at position index of a list  
// if 1 <= index <= size(). The list is  
// left unchanged by this operation.  
// Throws an exception if index is out of range.
```

The ADT List

- Specifications of the ADT operations
 - Define the contract for the ADT list
 - Do not specify how to store the list or how to perform the operations
 - If you request these operations be performed, this is what will happen.
 - ADT operations can be used in an application without the knowledge of how the operations will be implemented
-

Using an ADT.

The following methods manipulate the data in the list without knowing the implementation details of the List.

```
displayList(in aList:List) {
    for(index=1 through aList.size()) {
        dataItem=aList.get(index);
        Print dataItem;
    }
}

replace(in aList:List, in i:int, in
    newItem:ListItemType) {
    if(i>=1 and i<=aList.size()) {
        aList.remove(i);
        aList.insert(i, newItem);
    }
}
```

The ADT List




Figure 4-7

The wall between *`displayList`* and the implementation of the ADT list

The ADT Sorted List

- The ADT sorted list
 - Maintains items in sorted order
 - Inserts and deletes items by their values, not their positions

Pseudocode for the ADT Sorted List Operations

```
+createSortedList()  
// Creates an empty sorted list.  
  
+sortedIsEmpty():boolean {query}  
// Determines whether a sorted list is empty.  
  
+sortedSize():integer {query}  
// Returns the number of items that are in a sorted list.  
  
+sortedAdd(in item:ListItemType)  
// Inserts item into its proper sorted position in a  
// sorted list. Throws an exception if the item  
// cannot be placed on the list (list full).  
  
+sortedRemove(in item:ListItemType)  
// Deletes item from a sorted list.  
// Throws an exception if the item is not found.  
  
+sortedGet(in index:integer)  
// Returns the item at position index of a  
// sorted list, if  $1 \leq \text{index} \leq \text{sortedSize}()$ .  
// The list is left unchanged by this operation.  
// Throws an exception if the index is out of range.  
  
+locateIndex(in item:ListItemType):integer {query}  
// Returns the position where item belongs or  
// exists in a sorted list; item and the list are  
// unchanged.
```

Implementing ADTs

- Choosing the data structure to represent the ADT's data is a part of implementation
 - Choice of a data structure depends on
 - Details of the ADT's operations
 - Context in which the operations will be used
 - Implementation details should be hidden behind a wall of ADT operations
 - A program would only be able to access the data structure using the ADT operations
-

Implementing ADTs




Figure 4-8

ADT operations provide access to a data structure

Implementing ADTs




Figure 4-9

Wall of ADT operations

Violating the wall of ADT operations

An Array-Based Implementation of the ADT List

- An array-based implementation
 - A list's items are stored in an array `items`
 - A natural choice
 - Both an array and a list identify their items by number
 - A list's k^{th} item will be stored in `items[k-1]`

An Array-Based Implementation of




Figure 4-11

An array-based implementation of the ADT list

Create an Interface for the List ADT

```
public interface ListInterface{  
    public boolean isEmpty();  
    public int size();  
    public void add(int index, Object item) throws  
        ListException;  
    public Object get(int index) throws ListException;  
    public void remove(int index) throws ListException;  
    public void removeAll();  
}
```

Array-Based implementation.

```
public class ListArrayBased implements ListInterface{
    private static final int MAX_LIST = 50;
    private Object items[];
    private int numItems;

    public ListArrayBased(){ //act as the createList()
        items = new Objects[MAX_LIST];
        numItems = 0;
    }
    public boolean isEmpty(){
        return (numItems == 0);
    }
    public int size() {return numItems;}
    public void add(int index, Object item) throws
    ListException {...}
    public Object get(int index) throws ListException {...}
    public void remove(int index) throws ListException{...};
    public void removeAll(){...}
}
```

Using the List ADT

```
Static public void main() {  
    [...]  
    ListArrayBased groceryList = new ListArrayBased();  
    groceryList.add(1, "Milk");  
    [...]  
    String item=groceryList.get(1);  
  
    //violates the terms of abstraction.  
    String item=groceryList.items[0]; //illegal statement.  
  
    [...]  
}
```

Java Exceptions (review)

■ Exception

- ❑ A mechanism for handling an error during execution
 - ❑ A method indicates that an error has occurred by throwing an exception
 - ❑ When a method **throws** an exception the control of the program returns to the point at which the method is called.
 - ❑ At this point you must **catch** the exception and deal with it.
-

Java Exceptions –catching exception

- Java provides `try-catch` blocks to handle exceptions

- Syntax:

```
try{  
    statements;  
}  
catch (exceptionClass id) {  
    statements;  
}
```

- `try` block

- A statement that might throw an exception is placed within a `try` block
-

Java Exceptions

- Catching exceptions (Continued)

- `catch` block

- Used to catch an exception and deal with the error condition

- Syntax

```
catch (exceptionClass identifier) {  
    statement(s);  
} // end catch
```

```
try {  
    int result = 99/0; //this statement throws an exception  
    //other statements may appear here;  
} catch (ArithmeticException e) {  
    System.out.println("ArithmeticException caught");  
}
```

- When a statement throws an exception it returns an *object* that must be caught by the **catch** block.
 - When a statement in a try block **throws** an exception the remainder of the try block is abandoned, and the control is passed to the catch block that corresponds to the type of exception thrown.
-

Some exceptions must be handled.

```
public static void getInput(String filename){
    FileInputStream fis;
    fis = new FileInputStream(filename);
    [...]
}
```

- The **new** `FileInputStream` statement throws an exception if file is not found.
- In the above example this exception is not handled and therefore it won't get compiled.

```
public static void getInput(String filename){
    FileInputStream fis;
    try{
        fis = new FileInputStream(filename);
    }catch(FileNotFoundException e){
        System.out.println("The file"+filename+"Not found");
    }
    [...]
}
```

Java Exceptions

- Types of exceptions
 - Checked exceptions
 - Instances of classes that are subclasses of the `java.lang.Exception` class
 - Must be handled locally
 - Used in situations where the method has encountered a serious problem
-

Java Exceptions

- Types of exceptions (Continued)
 - Runtime exceptions
 - Used in situations where the error is not considered as serious
 - Can often be prevented by fail-safe programming
 - Instances of classes that are subclasses of the `RuntimeException` class
 - Are not required to be caught locally
-

Java Exceptions

- Throwing exceptions

- A `throw` statement is used to throw an exception

```
throw new exceptionClass (stringArgument);
```

- Defining a new exception class

- A programmer can define a new exception class
-

```
class MyException extends Exception {
    public MyException(String s) {
        super(s);
    } // end constructor
} // end MyException

public void myMethod() throws MyException{
    //some code here.
    if( some condition){
        throw new MyException("MyException: reason");
    }
}

public void yourMethod() {
    try{
        myMethod();
    }
    catch (MyException e){
        //code to handle the exception
    }
}
```

Finally block

■ The `finally` block

- ❑ Executed whether or not an exception is thrown
- ❑ Can be used even if no `catch` block is used

❑ Syntax

```
finally {  
    statement(s);  
}
```