

CMPT 225

Recursion-part 3

Recursive Searching

- Linear Search
 - Binary Search
 - Find an element in an array, return its position (index) if found, or -1 if not found.
-

Linear Search Algorithm (Java)


```
public int linSearch(int[] arr,  
                    int target)  
{  
    for (int i=0; i<arr.size; i++) {  
        if (target == arr[i]) {  
            return i;  
        }  
    } //for  
    return -1; //target not found  
}
```

Recursive Binary search

```
int recLinSearch (int[] arr, int low, int x)
```

To search the entire array for 2

```
index=recLinSearch(arr, 0, 2);
```



Recursive Linear Search Algorithm

- Base case
 - Found the target or
 - Reached the end of the array
- Recursive case
 - Call linear search on array from the next item to the end

```
public int recLinSearch(int[] arr, int low, int x) {  
    if (low >= arr.length) { // reach the end  
        return -1;  
    } else if (x == arr[low]) {  
        return low;  
    } else  
        return recLinSearch(arr, low + 1, x);  
}
```

How many comparison does the recLinSearch perform in worst case?

- Suppose $T(n)$ is the number of comparison where n is the size of the elements in the array.

- We have:

$$T(0)=0$$

$$T(n)=1+T(n-1)$$

- By expanding the $T(n)$ n times we have

$$T(n)=1+[1+T(n-2)]=2+T(n-2)=\dots=k+T(n-k)=\dots=n+T(0)=n=O(n)$$


- Thus, the recLinSearch is not more efficient than the non-recursive linear search.
-

Recursive linear search

```
int recBinSearch (int[] arr, int lower, int upper, int x)
```

To search the whole array for 2

```
index=recBinSearch(arr, 0 , arr.length, 2);
```



if $x < arr[mid]$

if $x > arr[mid]$

```
recBinSearch(arr, low, mid-1, x)    recBinSearch(arr, mid+1, upper, x)
```

Recursive Binary Search Algorithm

```
public int binSearch(  
    int[] arr, int lower, int upper, int x)  
{  
    int mid = (lower + upper) / 2;  
    if (lower > upper) { // empty interval  
        return - 1; // base case  
    } else if (arr[mid] == x) {  
        return mid; // second base case  
    } else if (arr[mid] < x) {  
        return binSearch(arr, mid + 1, upper, x);  
    } else { // arr[mid] > target  
        return binSearch(arr, lower, mid - 1, x);  
    }  
}
```

How many comparison does the `recBinSearch` perform in worst case?

- Suppose $T(n)$ is the number of comparison where n is the size of the elements in the array, and assume $n = 2^k$ (e.g. if $n = 128$, $k = 7$)

- We have:

$$T(1)=1$$

$$T(n)=1+T(n/2)$$

- By expanding the $T(n)$ n times we have

$$T(n)=1+[1+T(n/2)]=2+T(n/2)=\dots=k+T(n/2^k)=k+T(1)=k+1=O(\log_2 n)$$

Because $n = 2^k$, $k = \log_2 n$


Binary Search vs Linear Search

	<u>Linear</u>	<u>Binary</u>
<u>N</u>	<u>N</u>	<u>$\log_2(N)$</u>
10	10	4
100	100	7
1,000	1000	10
10,000	10,000	14
100,000	100,000	17
1,000,000	1,000,000	20
10,000,000	10,000,000	24

Processing linked list recursively.

- It's possible and sometimes desirable to process linked list recursively.
- Eg. Displaying the elements in the list recursively.

`writeList(Node cur)` : displays the elements from `cur` to the end of the list.



```
private void writeList(Node cur) {  
    if (cur==null)  
        return;  
    System.out.println(cur.getItem());  
    writeList(cur.getNext());  
}
```

$$T(n) = 1 + T(n-1)$$

$$T(0) = 0$$

Writing a list backward.

- A non-recursive solution.

```
private void writeListBackward1() {  
    Object temp[] = new Object[size];  
    Node cur = head;  
    for(int i=0; i<size; i++, cur=cur.getNext())  
        temp[i] = cur.getItem();  
    for(int i=size-1; i>=0; i--)  
        System.out.println(temp[i]);  
}
```

- Needs an extra array of the same size as list.
 - The space complexity is $O(n)$ –where n is the size of the array
-

Writing a list backward-a new solution.


```
private void writeListBackward2 () {  
    for(int i=size-1; i>=0; i--) {  
        //returns the reference to the ith element in the  
        //list.  
        Node cur=get(i);  
        System.out.println(cur.getItem());  
    }  
}
```

- Does not need extra space.
 - The space complexity is $O(1)$
 - However, it's slow
 - The `get(i)` method requires i operations.
 - Therefore, the total number of operations: $(n-1)+(n-2)+\dots+1=O(n^2)$
-

Writing a list backward-a recursive solution.

`writeListBackwardRec(Node cur)` : displays the elements from `cur` to the end of the list in a reverse order.

12 4 7 6 1



```
private void writeListBackwardRec(Node cur) {  
    if (cur == null)  
        return;  
    writeListBackwardRec(cur.getNext());  
    System.out.println(cur.getItem());  
}
```

The time complexity is $O(n)$, therefore it's an optimal solution in terms of time.

What is the space complexity?

- Is it $O(1)$?
 - No!!!. It requires a *stack* of size $O(n)$ when it's executed.
-

```

public void displayBackward() {
    writeListBackwardRec(head); //Z
}

```


```

private void writeListBackwardRec(Node cur) {
    if (cur == null)
        return;
    writeListBackwardRec(cur.getNext()); //X
    System.out.println(cur.getItem()); //Y
}


```

Call Stack


Cur:nul Ret:x
Cur:12 Ret:X
Cur:7 Ret:X
Cur:6 Ret:X
Cur:1 Ret:Z



The optimal solution.




Reverse the list.



Print the reversed list.

Restore the list to original order



$O(n)$: time, $O(1)$:space

$O(n)$: time, $O(1)$:space

$O(n)$: time, $O(1)$:space

Total $O(n)$: time, $O(1)$:space

Recursion Disadvantage 1


- Recursive algorithms have more overhead than similar iterative algorithms
 - Because of the repeated method calls (storing and removing data from call stack)
 - This may also cause a “stack overflow” when the call stack gets full
 - It is often useful to derive a solution using recursion and implement it iteratively
 - Sometimes this can be quite challenging!
(Especially, when computation continues after the recursive call -> we often need to remember value of some local variable -> stacks can be often used to store that information.)
-

Recursion Disadvantage 2

- Some recursive algorithms are inherently inefficient
 - An example of this is the recursive Fibonacci algorithm which repeats the same calculation again and again
 - Look at the number of times fib(2) is called
 - Even if the solution was determined using recursion such algorithms should be implemented iteratively
 - To make recursive algorithm efficient:
 - Generic method (used in AI): store all results in some data structure, and before making the recursive call, check whether the problem has been solved.
 - Make iterative version.
-

Function Analysis for call **fib(5)**

```
public static int fib(int n)
  if (n == 0 || n == 1)
    return n
  else
    return fib(n-1) + fib(n-2)
```



Iterative Fib solution

```
int itrFib(int n) {  
    int F0=0, F1=1, F2=0;  
    for(int i=0; i<n; i++) {  
        F2=F0+F1;  
        F0=F1;  
        F1=F2;  
    }  
    return F2;  
}
```

Generic Fib Solution

```
int genericFib(int n) {  
    if (n==0 || n==1)  
        return n;  
    if (globalFib[n]>=0)  
        return globalFib[n];  
    globalFib[n]=genericFib(n-1)+genericFib(n-2);  
    return globalFib[n];  
}
```

- **The globalFib is a global array that is initially set to -1.**
-



Analyzing Recursive Functions

- Recursive functions can be tricky to analyze
 - It is useful to trace through the sequence of recursive calls
 - This can be done using a recursion tree
 - As shown for the Fibonacci function
 - Recursion trees can also be used to determine the running time (in number of operations) of algorithms
 - Annotate the tree to indicate how much work is performed at each level of the tree
 - Determine how many levels of the tree there are
-

Recursion and Induction

- Recursion is similar to mathematical induction as recursion solves a problem by
 - Specifying a solution for the base case and
 - Using the recursive case to derive solutions of any size from the solutions to smaller problems
 - Induction proves a property by
 - Proving it is true for a base case (which is often true by definition) and
 - Proving that it is true for some number, n , if it is true for all numbers less than n
-

Recursive Factorial Algorithm

```
public int fact (int x) {  
    // Should check for negative values of x  
    if (x == 0) {  
        return 1;  
    } else  
        return x * fact(x - 1);  
}
```

- Prove, using induction, that the algorithm returns the values:
 - $\text{fact}(0) = 0! = 1$
 - $\text{fact}(n) = n! = n * (n - 1) * (n - 2) * \dots * 1$ if $n > 0$

Proof by Induction of **fact** Method

- **Basis:** Show that the property is true for $n = 0$, i.e. that `fact(0)` returns 1
 - This is true by definition as `fact(0)` is the base case of the algorithm and returns 1
 - Now establish that the property is true for an arbitrary k implies that it is true for $k + 1$
 - **Inductive hypothesis:** Assume that the property is true for $n = k$, that is assume that
 - $\text{fact}(k) = k * (k - 1) * (k - 2) * \dots * 2 * 1$
-

Proof by Induction of **fact** Method

- **Inductive conclusion:** Show that the property is true for $n = k + 1$, i.e., that $\text{fact}(k + 1)$ returns
 - $(k + 1) * k * (k - 1) * (k - 2) * \dots * 2 * 1$
 - By definition of the function $\text{fact}(k + 1)$ returns
 - $(k + 1) * \text{fact}(k)$ – the recursive case
 - And by the inductive hypothesis $\text{fact}(k)$ returns
 - $k * (k - 1) * (k - 2) * \dots * 2 * 1$
 - Therefore $\text{fact}(k + 1)$ must return
 - $(k + 1) * k * (k - 1) * (k - 2) * \dots * 2 * 1$
 - Which completes the inductive proof
-