


cmpt-225

Sorting – Part two

Idea of Quick Sort

- 1) **Select**: pick an element
- 2) **Divide**: partition elements so that x goes to its final position E
- 3) **Conquer**: recursively sort left and right partitions




Quick Sort - algorithm



```
public void QuickSort(Comparable[] arr, int low, int
high) {
    if (low <= high) // if size <= 1 already sorted
        return;
    else // size is 2 or larger
    {
        // partition range
        int pivotIndex = partition(arr, low, high);
        // sort left subarray
        QuickSort(arr, low, pivotIndex - 1);
        // sort right subarray
        QuickSort(arr, pivotIndex + 1, high);
    }
}
```

Quick Sort - Partitioning

- A key step in the Quick sort algorithm is **partitioning** the array
 - We choose some (any) number p in the array to use as a **pivot**
 - We **partition** the array into three parts:




Quick Sort – Partitioning



Partitioning using an extra array.

85	24	63	45	17	31	96	50
----	----	----	----	----	----	----	----

Put the smaller elements in front of the temporary array and the larger element in the back




24	45	17	31	50	96	63	85
----	----	----	----	----	----	----	----

Return the temporary array


Quick Sort – Partitioning – algorithm

Index l scans the sequence from the left, and index r from the right.




Increment l until $arr[l]$ is larger than the pivot; and decrement r until $arr[r]$ is smaller than the pivot.


Then swap elements indexed by l and r . Repeat until whole array is processed.



Quick Sort – Partitioning – algorithm



A final swap with the pivot completes the partitioning.



Quick Sort – Partitioning – algorithm


```
public int partition(Comparable[] arr, int low, int high) {
    Comparable pivot = arr[high]; // choose pivot
    int l = low;
    int r = high-1;
    while (l<=r) {
        // find bigger item on the left
        while (l<=r && arr[l].compareTo(pivot) <= 0)
            l++;

        // find smaller item on the right
        while (l<=r && arr[r].compareTo(pivot) >= 0)
            r--;


        if (l<r) {
            swap(arr[l], arr[r]);
            l++;
            r--;
        }
    }
    // put pivot to the correct location
    swap(arr[l], arr[high]);
    return l;
}
```

Quick Sort – Partitioning – another algorithm (textbook)

- Pivot is chosen to be the first element of the array (does not really matter)
- The array is divided to 4 parts (see below), initially “<p” and “≥p” parts are empty
- Invariant for the partition algorithm:
The items in region S_1 are all less than the pivot, and those in S_2 are all greater than or equal to the pivot
- In each step the first element in “?” part is added either to “<p” or “≥p” part.



Quick Sort – Partitioning – another algorithm (textbook)



S_1 : $\text{arr}[\text{first}+1].. \text{arr}[\text{lastS1}]$

) empty

S_2 : $\text{arr}[\text{lastS1}+1].. \text{arr}[\text{firstUnknown}-1]$


) empty

?: $\text{arr}[\text{firstUnknown}].. \text{arr}[\text{last}]$

) all elements but pivot




Initial state of the array

Quick Sort – Partitioning – another algorithm (textbook)




Processing `arr[firstUnknown]`: case “`< pivot`”

Move `arr[firstUnknown]` into S_1 by swapping it with `theArray[lastS1+1]` and by incrementing both `lastS1` and `firstUnknown`.



Quick Sort – Partitioning – another algorithm (textbook)



Processing `arr[firstUnknown]`: case “ $\geq$ pivot”

Moving *theArray[firstUnknown]* into S_2 by incrementing *firstUnknown*.

Quick Sort – Selection of pivot




- In the above algorithm we selected the pivot to be the last or the first element of subarray which we want to partition
 - It turns out that the selection of pivot is crucial for performance of Quick Sort – see best and worst cases
 - Other strategies used:
 - select 3 (or more elements) and pick the median
 - randomly select (especially used when the arrays might be originally sorted)
 - select an element “close to the median” in the subarray
-

Analysis of Quick Sort:

Best Case

- How much time do we need to partition an array of size n ?
 - $O(n)$ using any of two algorithms
 - **Best case:** Suppose each partition operation divides the array almost exactly in half
-

Best case Partitioning at various levels



Analysis of Quick Sort:

Best Case

- How much time do we need to partition an array of size n ?
 - $O(n)$ using any of two algorithms
 - **Best case:** Suppose each partition operation divides the array almost exactly in half
 - When could the best case happen?
 - For example, array was sorted and the pivot is selected to be the middle element of the subarray.
-

Analysis of Quick Sort:

Best Case

- **Best case:** Suppose each partition operation divides the array almost exactly in half
- The running time (time cost) can be expressed with the following recurrence:

$$\begin{aligned} T(n) &= 2.T(n/2) + \\ &\quad T(\text{partitioning array of size } n) \\ &= 2.T(n/2) + O(n) \end{aligned}$$

- The same recurrence as for merge sort, i.e., $T(n)$ is of order $O(n \log n)$.
-

Analysis of Quick Sort:

Worst Case

- In the worst case, partitioning always divides the size n array into these three parts:
 - A length one part, containing the pivot itself
 - A length zero part, and
 - A length $n-1$ part, containing everything else
-

Worst case partitioning



Analysis of Quick Sort:

Worst Case

- In the worst case, partitioning always divides the size n array into these three parts:
 - A length one part, containing the pivot itself
 - A length zero part, and
 - A length $n-1$ part, containing everything else
 - When could this happen?
 - Example: the array is sorted and the pivot is selected to be the first or the last element.
-

Analysis of Quick Sort:

Worst Case

- The recurrent formula for the time cost of Quick Sort in the worst case:

$$\begin{aligned}T(n) &= T(0) + T(n-1) + O(n) \\ &= T(n-1) + O(n)\end{aligned}$$

- By repeated substitution (or Master's theorem) we get the running time of Quick Sort in the worst case is $O(n^2)$
 - Similar, situation as for Insertion Sort. Does it mean that the performance of Quick Sort is bad on average?
-

Quick Sort:

Average Case

- If the array is sorted to begin with, Quick sort running time is terrible: $O(n^2)$
(Remark: could be improved by random selection of pivot.)
 - It is possible to construct other bad cases
 - However, Quick sort runs *usually* (on average) in time $O(n \log_2 n)$
-> CMPT307 for detailed analysis
 - The constant in front of $n \log_2 n$ is so good that Quick sort is generally the fastest algorithm known.
 - Most real-world sorting is done by Quick sort.
-

Exercise Problem on Quick Sort.

1. What is the running time of QUICKSORT when
 - a) All elements of array A have the same value ?
 - b) The array A contains distinct elements and in sorted decreasing order ?
-

Answer – 1st algorithm

- Pivot is chosen to be the last element in the subarray.
 - a) Whatever **pivot** you choose in each subarray it would result in WORST CASE PARTITIONING ($l=high$) and hence the running time is $O(n^2)$.
 - b) Same is the case. Since you always pick the minimum element in the subarray as the **pivot** each partition you do would be a worst case partition and hence the running time is $O(n^2)$ again !
-

Answer – 2nd algorithm


- Pivot is chosen to be the first element in the subarray
 - a) Whatever **pivot** you choose in each subarray it would result in WORST CASE PARTITIONING (everything will be put to S_2 part) and hence the running time is $O(n^2)$.
 - b) Same is the case. Since you always pick the maximum element in the sub array as the **pivot** each partition you do would be a worst case partition and hence the running time is $O(n^2)$ again !
-

Finding the k-th Smallest Element in an Array (Selection Problem)

- One possible strategy: sort an array and just take the k-th element in the array
 - This would require $O(n \log n)$ time if use some efficient sorting algorithm
 - Question: could we use partitioning idea (from Quicksort)?
-

Finding the k-th Smallest Element in an Array

- Assume we have partitioned the subarray as before.



If S_1 contains k or more items $\rightarrow$ S_1 contains k th smallest item

If S_1 contains $k-1$ items $\rightarrow$ k -th smallest item is pivot p

If S_1 contains fewer than $k-1$ items $\rightarrow$ S_2 contains k th smallest item

Finding the k-th Smallest Element in an Array

```
public Comparable select(int k, Comparable[] arr, int low, int high)
// pre: low <= high  and
//       k <= high-low+1 (number of elements in the subarray)
// return the k-th smallest element
// of the subarray arr[low..high]
{
    int pivotIndex = partition(arr, low, high);
    // Note: pivotIndex - low is the local index
    //       of pivot in the subarray
    if (k == pivotIndex - low + 1) {
        // the pivot is the k-th element of the subarray
        return arr[pivotIndex];
    } else if (k < pivotIndex - low + 1) {
        // the k-th element must be in S1 partition
        return select(k, arr, low, pivotIndex-1);
    } else { // k > pivotIndex - low + 1
        // the k-th element must be in S2 partition
        // Note: there are pivotIndex-first elements in S1
        //       and one pivot, i.e., all smaller than
        //       elements in S2, so we have to recalculate
        //       index k
        return select(k - (pivotIndex-first+1), arr, pivotIndex+1, high);
    }
} // end kSmall
```

Finding the k-th Smallest Item in an Array

- The running time in the best case:
 $T(n) = T(n/2) + O(n)$
 - It can be shown with repeated substitution that $T(n)$ is of order $O(n)$
 - The running time in the worst case:
 $T(n) = T(n-1) + O(n)$
 - This gives the time $O(n^2)$
 - average case: $O(n)$
 - By selecting the pivot close to median (using a recursive linear time algorithm), we can achieve $O(n)$ time in the worst case as well.
-

Radix Sort

- Treats each data item as a character string.
- The data items are all of the same length K, if not pad the shorter strings with blank characters (or 0 digits) on the right (on the left).

AC, CBC, JKP, O, CF

AC**b**, CBC, JKP, O**bb**, CF**b** //padding with blanks

12, 345, 5, 678, 226

012, 345, **00**5, 678, **0**26 //padding with 0's

-
- Idea: forming groups and combine them.

ABC, XYZ, BWZ, AAC, RLT, JBX, RDT, KLT, AEO, TLJ

- Group based on the last character:

C: ABC, AAC

J: TLJ

O: AEO

T: RLT, RDT, KLT

X: JBX

Z: XYZ, BWZ

- Combine the groups.

ABC, AAC, TLJ, AEO, RLT, RDT, KLT, JBX, XYZ, BWZ

- Regroup based on second character

(AAC) (ABC, JBX) (RDT) (AEO) (TLJ, RLT, KLT) (BWZ) (XYZ)

- Combine groups base on first character

AAC, **ABC**, **JBX**, **RDT**, **AEO**, **TLJ**, **RLT**, **KLT**, **BWZ**, **XYZ**

- Regroup based on first character

(**AAC**, **ABC**, **AEO**)(**BWZ**)(**JBX**)(**KLT**)(**RDT**, **RLT**)(**TLJ**)(**XYZ**)

- Combine groups

AAC, ABC, AEO, BWZ, JBX, KLT, RDT, RLT, TLJ, XYZ

Complexity of Radix sort.

- We do the grouping and combining procedure K times, where K is the length of the strings.
 - Each grouping and combining pass takes $O(n)$ time.
 - The whole sort takes $O(Kn)$ time.
 - If K is constant the Radix sort is $O(n)$.
-

A Comparison of Sorting Algorithms

	<u>Worst case</u>	<u>Average case</u>
Selection sort	n^2	n^2
Bubble sort	n^2	n^2
Insertion sort	n^2	n^2
Mergesort	$n * \log n$	$n * \log n$
Quicksort	n^2	$n * \log n$
Radix sort	n	n
Treesort	n^2	$n * \log n$
Heapsort	$n * \log n$	$n * \log n$

Approximate growth rates of time required for eight sorting algorithms

